

Amendments to the Specification

Please amend the specification, as follows:

Page 1, replace the title paragraph with the following amended paragraph:

~~CARCASS STRUCTURE FOR TYRES AND TYRE HAVING THE~~ FOR A TWO-
WHEELED VEHICLE AND CARCASS STRUCTURE FOR THE TYRE

Delete the ABSTRACT OF THE DISCLOSURE in its entirety and replace it with the following new ABSTRACT OF THE DISCLOSURE. A new, separate ABSTRACT OF THE DISCLOSURE is enclosed, labeled as page 35.

ABSTRACT OF THE DISCLOSURE

A carcass structure for a two-wheeled vehicle tyre includes at least one carcass ply and a pair of annular reinforcing structures. The at least one carcass ply includes a first series and at least one second series of strip sections circumferentially distributed in a mutually-alternated sequence around a geometric rotation axis of the tyre. Each strip section includes longitudinal and parallel thread elements at least partly coated with at least one layer of elastomer material and extends in a substantially U-shaped configuration to define two side portions and a crown portion. The annular reinforcing structures are applied against end flaps of the first series of strip sections and are overlapped by end flaps of the at least one second series of strip sections. Each

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

of the annular reinforcing structures includes an annular anchoring insert, including one or more elongated elements extending in radially-concentric coils, and at least one filling body.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com